

CODE:	8007
--------------	-------------

PRODUCT:	COUCHE PREMIUM AP718 GL55
-----------------	----------------------------------

SET	DESCRIPTION						
	Self-adhesive glossy couche paper, recommended for transformation on rotating machines. Perfect for multi-color printing systems requiring excellent graphic quality. Material not recommended for processing into sheets.						
	<table> <tr> <td>GRAMMAGE</td> <td>g/ m²</td> <td>163 ± 9</td> </tr> <tr> <td>THICKNESS</td> <td>µm</td> <td>146 ± 11</td> </tr> </table>	GRAMMAGE	g/ m ²	163 ± 9	THICKNESS	µm	146 ± 11
GRAMMAGE	g/ m ²	163 ± 9					
THICKNESS	µm	146 ± 11					

FRONT	DESCRIPTION						
COUCHE GLOSSY	Double-layer coated glossy couche paper perfect for multi-color printing systems requiring excellent graphic quality, provided proper inks and printing technologies are used.						
	<table> <tr> <td>GRAMMAGE</td> <td>g/ m²</td> <td>90 ± 4</td> </tr> <tr> <td>THICKNESS</td> <td>µm</td> <td>77 ± 4</td> </tr> </table>	GRAMMAGE	g/ m ²	90 ± 4	THICKNESS	µm	77 ± 4
GRAMMAGE	g/ m ²	90 ± 4					
THICKNESS	µm	77 ± 4					

ADHESIVE	DESCRIPTION																		
AP718	Permanent acrylic adhesive in aqueous emulsion. It has good initial adhesiveness and great final adhesiveness. It can be used on various types of substrates, such as glass, paper, metal surfaces and packaging.																		
	We do not recommend using this adhesive on hard-to-stick substrates such as textured, uneven or porous surfaces and surfaces with non-stick properties.																		
	<table> <tr> <td>GRAMMAGE</td> <td>g/ m²</td> <td>18 ± 2</td> </tr> <tr> <td>TACK</td> <td>g/25mm</td> <td>Minimum 900</td> </tr> <tr> <td>ADHESIVENESS</td> <td>g/25mm</td> <td>Minimum 1000</td> </tr> <tr> <td>RELEASE 180°</td> <td>g/25mm</td> <td>5 to 20</td> </tr> <tr> <td>TEMP. OF APPLICATION</td> <td>°C</td> <td>+ 10</td> </tr> <tr> <td>RESIST. TO TEMPERATURE</td> <td>°C</td> <td>-10 to +120</td> </tr> </table>	GRAMMAGE	g/ m ²	18 ± 2	TACK	g/25mm	Minimum 900	ADHESIVENESS	g/25mm	Minimum 1000	RELEASE 180°	g/25mm	5 to 20	TEMP. OF APPLICATION	°C	+ 10	RESIST. TO TEMPERATURE	°C	-10 to +120
GRAMMAGE	g/ m ²	18 ± 2																	
TACK	g/25mm	Minimum 900																	
ADHESIVENESS	g/25mm	Minimum 1000																	
RELEASE 180°	g/25mm	5 to 20																	
TEMP. OF APPLICATION	°C	+ 10																	
RESIST. TO TEMPERATURE	°C	-10 to +120																	

LINER	DESCRIPTION						
GL55	Supercalendered, translucent, high tensile and tear resistance glassline type paper with a siliconized face. Recommended for applications in processes that require light passage (optical reading) and automatic labelers where a high mechanical resistance and regularity of thickness is required for the cutting medium.						
	<table> <tr> <td>GRAMMAGE</td> <td>g/ m²</td> <td>55 ± 3</td> </tr> <tr> <td>THICKNESS</td> <td>µm</td> <td>51 ± 4</td> </tr> </table>	GRAMMAGE	g/ m ²	55 ± 3	THICKNESS	µm	51 ± 4
GRAMMAGE	g/ m ²	55 ± 3					
THICKNESS	µm	51 ± 4					

STOCK WARRANTY: This product has a warranty of 01 year as long as it remains stored in its original packaging, conditioned at a temperature of 23 ± 2°C and relative humidity of 65 ± 10%.

ATTENTION: All of the above information regarding **PROTACK** products is for guidance only. We recommend adapting the indications on the use of our products to local conditions, taking into account the materials and/or substrates to be used. If you have questions as to the application, contact our Technical Department. We reserve the right to make improvements and modifications to these products without prior notice.